NSN 5945-01-201-7432

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-201-7432 **Overall Length:** 0.787 inches **Overall Height:** 0.524 inches Overall Width: 0.390 inches **Environmental Protection:** Shock resistant and vibration resistant and hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 1.6 kilohms all windings **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Time Delay: 0.003 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 24.0 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 3.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 250.0 ac and 220.0 dc **Energizing Element Power Rating:** 400.0 milliwatts **Precious Material And Location:** Contact surfaces gold and contacts silver **Precious Material:** Gold and silver **Terminal Type And Quantity:** 10 pin all functions Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5945-01-201-7432

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300