

View Online at <https://aerobasegroup.com/nsn/5945-01-202-4338>

Thread Class:

2a single mounting facility

Overall Length:

0.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches single mounting facility

Overall Height:

1.315 inches

Overall Width:

0.810 inches

Environmental Protection:

Shock resistant and vibration resistant

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

600.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Features Provided:

Coil voltage suppression and latching contacts

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Time Delay:

0.006 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.500 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.5 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

13 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300