NSN 5945-01-202-8363

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-202-8363

Overall Length:
0.280 inches
Overall Diameter:
0.370 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
Specific
Coil Quantity:
1
Winding Dc Resistance Rating:
125.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Storage Type:
General purpose warehouse
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.002 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Failure rate level 3.0 percent
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5945-01-202-8363

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quan	tity:
------------------------	-------

5 wire lead all functions

Specification Data:

81349-mil-r-39016/7 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300