NSN 5945-01-203-6041

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-203-6041

| Overall Length: | | |
|---|--|--|
| 3.225 inches | | |
| Overall Height: | | |
| 0.900 inches | | |
| Overall Width: | | |
| 1.115 inches | | |
| Case Material: | | |
| Plastic | | |
| Fragility Factor: | | |
| Moderately rugged | | |
| Winding Quantity: | | |
| 1 | | |
| Purpose For Which Designed: | | |
| General | | |
| Coil Quantity: | | |
| 1 | | |
| Winding Dc Resistance Rating: | | |
| 70.0 ohms single winding | | |
| Duty Type: | | |
| Continuous | | |
| Arc Quenching Method: | | |
| Air | | |
| Mounting Facility Type And Quantity: | | |
| 1 plug-in terminal single mounting facility | | |
| Storage Type: | | |
| General purpose warehouse | | |
| Features Provided: | | |
| Polarized | | |
| Cubic Measure: | | |
| 3.236 cubic inches | | |
| Nonpile-up Main Contact Arrangement: | | |
| 2 two circuit, double break/double make, one position momentary | | |
| Time Delay: | | |
| 0.0065 seconds fixed operate and release time | | |
| Operating Voltage Rating And Type At Specificationified Temp: | | |
| 12.0 volts dc 25 degrees celsius single winding | | |
| Main Contact Load Current Rating At Maximum Rated Voltage: | | |
| 5.0 amperes dc resistive load | | |
| Main Contact Maximum Voltage Rating In Volts: | | |
| 500.0 dc | | |
| | | |

12 pin all functions

NSN 5945-01-203-6041

Electromagnetic Relay - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300