NSN 5945-01-204-6920

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-204-6920

Overall Length:

1.330 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.068 inches single mounting facility and 1.088 inches single mounting facility

Overall Height:

Between 0.390 inches and 0.410 inches

Overall Width:

0.410 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.110 inches single mounting facility and 0.130 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

1.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Features Provided:

Latching contacts

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 pin all functions

Specification Data:

36659-Is15474 manufacturers standard

Shelf Life:

N/a

NSN 5945-01-204-6920

Electromagnetic Relay - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A03300