## NSN 5945-01-205-3332

Electromagnetic Relay - Page 1 of 2

Operating Current Rating And Type: 150.0 milliamperes dc single winding

Overall Length: 1.718 inches



View Online at https://aerobasegroup.com/nsn/5945-01-205-3332

Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
1.300 inches
Overall Width:
1.030 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
Navy equip
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
2.300 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary

## NSN 5945-01-205-3332

Electromagnetic Relay - Page 2 of 2



Time D	elay:
--------	-------

20.00 seconds fixed release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

**Energizing Element Power Rating:** 

1.5 watts

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

-

Demilitarization:

No

Fiig:

A03300