

View Online at <https://aerobasegroup.com/nsn/5945-01-205-3332>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

1.300 inches

**Overall Width:**

1.030 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**End Application:**

Navy equip

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Cubic Measure:**

2.300 cubic inches

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

150.0 milliamperes dc single winding

**Time Delay:**

20.00 seconds fixed release time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Energizing Element Power Rating:**

1.5 watts

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

8 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300