NSN 5945-01-206-1088

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-206-1088

Overall Length:
1.200 inches
Overall Height:
0.600 inches
Overall Width:
0.750 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.540
0.540 cubic inches
Nonpile-up Main Contact Arrangement:
Nonpile-up Main Contact Arrangement:
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay:
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay: 0.01 seconds fixed operate and release time
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay: 0.01 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp:
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay: 0.01 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 115.0 volts ac 25 degrees celsius single winding
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay: 0.01 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay: 0.01 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 8.0 amperes ac resistive load and 4.0 amperes dc resistive load
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay: 0.01 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 8.0 amperes ac resistive load and 4.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action and 1 pole, single throw, normally open, momentary action Time Delay: 0.01 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 8.0 amperes ac resistive load and 4.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc

N/a

NSN 5945-01-206-1088

Electromagnetic Relay - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A03300