## NSN 5945-01-208-4942

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-208-4942

View Online at https://aerobasegroup.com/nsn/5945-01-208-4942
Overall Length:
0.810 inches
Overall Height:
0.410 inches
Overall Width:
0.410 inches
Environmental Protection:
Hermetic and shock resistant and vibration resistant
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Features Provided:
Coil voltage suppression
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.005 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
160.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Failure rate level 0.1 percent
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 pin all functions

81349-mil-r-39016/22 government specification **Shelf Life:** 

**Specification Data:** 

N/a

## NSN 5945-01-208-4942

Electromagnetic Relay - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300