## NSN 5945-01-209-0402

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-209-0402

Thread Class:
2a mounting facility bushing
Thread Direction:
Right-hand mounting facility bushing
Body Style:
Cylindrical frame
Body Diameter:
1.880 inches
Body Length:
3.500 inches
Case Material:
Metal
Environmental Protection:
Any acceptable
Actuator Length:
1.438 inches
Fragility Factor:
Moderately rugged
Actuator Width:
0.380 inches
Inclosure Type:
Inclosure Type: Fully enclosed
Fully enclosed
Fully enclosed  Magnetic Coil Quantity:
Fully enclosed  Magnetic Coil Quantity:
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type:
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type:  Continuous
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type:  Continuous  Terminal Location:
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type:  Continuous  Terminal Location:  Circumference
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type:  Continuous  Terminal Location:  Circumference  Voltage Rating In Volts:
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity:
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity: 1 threaded bushing
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity: 1 threaded bushing  Storage Type:
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity: 1 threaded bushing  Storage Type: General purpose warehouse
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity: 1 threaded bushing  Storage Type: General purpose warehouse  Thready Qty Per Inch (tpi):
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity: 1 threaded bushing  Storage Type: General purpose warehouse  Thready Qty Per Inch (tpi): 20 mounting facility bushing
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity: 1 threaded bushing  Storage Type: General purpose warehouse  Thready Qty Per Inch (tpi): 20 mounting facility bushing  Actuator Stroke Type:
Fully enclosed  Magnetic Coil Quantity:  1  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 24.0 dc  Mounting Facility Type And Quantity: 1 threaded bushing  Storage Type: General purpose warehouse  Thready Qty Per Inch (tpi): 20 mounting facility bushing  Actuator Stroke Type: Pull

Flatted-drilled

## NSN 5945-01-209-0402

Electrical Solenoid - Page 2 of 2



## Energizing Stroke Maximum Length: 0.125 inches Thread Size: 1.250 inches mounting facility bushing Thread Series Designator: Uns mounting facility bushing Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A134a0