NSN 5945-01-209-2225

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-209-2225
Overall Length:
1.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Overall Height:
1.405 inches
Overall Width:
0.525 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Metal
Contact Surface Treatment:
Gold
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Winding Dc Resistance Rating:
600.0 ohms all windings
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Footures Provided:

Features Provided:

Polarized and latching contacts and coil voltage suppression

Cubic Measure:

1.267 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

NSN 5945-01-209-2225

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary **Operating Current Rating And Type:** 50.0 milliamperes dc all windings Time Delay: 0.01 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 15.0 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 28.0 dc **Precious Material And Location:** Contacts gold **Precious Material: Terminal Type And Quantity:** 7 pin all functions Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A03300