### NSN 5945-01-210-5333



E	lectromagnetic Relay - Page 1 of 2	
Vi	iew Online at https://aerobasegroup.com/nsn/5945-01-210-5333	
0	verall Length:	
1.	.718 inches	
C	enter To Center Distance Between Mounting Facilities Parallel To Length:	
1.	396 inches single mounting facility and 1.446 inches single mounting facility	
0	verall Height:	
1.	655 inches	
0	verall Width:	
0.	525 inches	
M	ounting Slot Width:	
0.	150 inches single mounting facility	
C	ase Material:	
М	letal	
E	nvironmental Protection:	
Н	ermetic	
Fı	ragility Factor:	
М	loderately rugged	
W	/inding Quantity:	
1		
P	urpose For Which Designed:	
G	eneral	
C	oil Quantity:	
1		
W	/inding Dc Resistance Rating:	
1.	04 kilohms single winding	
D	uty Type:	
C	ontinuous	
A	rc Quenching Method:	
Ai	ir	
M	ounting Facility Type And Quantity:	
2	slotted hole single mounting facility	
St	torage Type:	
_	anaral purpose warehouse	

General purpose warehouse

## **Cubic Measure:**

1.493 cubic inches

### **Mounting Facility Pattern:**

In-line single mounting facility

#### **Nonpile-up Main Contact Arrangement:**

1 pole, double throw, one position momentary

#### Time Delay:

0.05 seconds fixed release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

# NSN 5945-01-210-5333

Electromagnetic Relay - Page 2 of 2



#### Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac

**Terminal Type And Quantity:** 

5 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300