NSN 5945-01-210-6307



| Electromagnetic Relay - Page 1 of 2 | Grou |
|--|-------------------------|
| View Online at https://aerobasegroup.com/nsn/5945-01-210-6307 | |
| Overall Length: | |
| 1.310 inches | |
| Overall Height: | |
| 0.390 inches | |
| Overall Width: | |
| 0.480 inches | |
| Environmental Protection: | |
| Hermetic and shock resistant and vibration resistant | |
| Winding Quantity: | |
| 1 | |
| Coil Quantity: | |
| 1 | |
| Winding Dc Resistance Rating: | |
| 390.0 ohms single winding | |
| Duty Type: | |
| Continuous | |
| Mounting Facility Type And Quantity: | |
| 1 terminal single mounting facility | |
| Nonpile-up Main Contact Arrangement: | |
| 4 pole, double throw, one position momentary | |
| Criticality Code Justification: | |
| Feat | |
| Time Delay: | |
| 0.005 seconds fixed operate and release time | |
| Operating Voltage Rating And Type At Specificationified Temp: | |
| 26.5 volts dc 25 degrees celsius single winding | |
| Main Contact Load Current Rating At Maximum Rated Voltage: | |
| 300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load | |
| Main Contact Maximum Voltage Rating In Volts: | |
| 115.0 ac and 28.0 dc | |
| Special Features: | |
| Failure rate level 1.0 | |
| Test Data Document: | |
| 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type | e data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type | e data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) | |
| Terminal Type And Quantity: | |
| | |

14 wire hook all functions

Specification Data:

81349-mil-r-39016/40 government specification

Shelf Life:

N/a

Unit Of Measure:

NSN 5945-01-210-6307

Electromagnetic Relay - Page 2 of 2

Demilitarization:

No

Fiig:

A03300

