NSN 5945-01-210-9107

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-210-9107

| Overall Length: | | |
|---|--|--|
| 3.875 inches | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | |
| 2.375 inches single mounting facility | | |
| Overall Height: | | |
| 3.125 inches | | |
| Overall Width: | | |
| 2.500 inches | | |
| Case Material: | | |
| Plastic | | |
| Unthreaded Mounting Hole Diameter: | | |
| 0.171 inches single mounting facility | | |
| Fragility Factor: | | |
| Moderately rugged | | |
| Winding Quantity: | | |
| 1 | | |
| Purpose For Which Designed: | | |
| General | | |
| Coil Quantity: | | |
| 1 | | |
| Duty Type: | | |
| Continuous | | |
| Arc Quenching Method: | | |
| Air | | |
| Mounting Facility Type And Quantity: | | |
| 2 unthreaded hole single mounting facility | | |
| Storage Type: | | |
| General purpose warehouse | | |
| Cubic Measure: | | |
| 30.273 cubic inches | | |
| Mounting Facility Pattern: | | |
| In-line single mounting facility | | |
| Nonpile-up Main Contact Arrangement: | | |
| 2 pole, single throw, normally open, momentary action | | |
| Operating Voltage Rating And Type At Specificationified Temp: | | |
| 240.0 volts ac 25 degrees celsius single winding | | |
| Main Contact Load Current Rating At Maximum Rated Voltage: | | |
| 2.0 amperes ac resistive load and 1.0 amperes dc resistive load | | |
| Main Contact Maximum Voltage Rating In Volts: | | |
| 120.0 ac and 28.0 dc | | |
| Terminal Type And Quantity: | | |

6 screw all functions

NSN 5945-01-210-9107

Electromagnetic Relay - Page 2 of 2



| | Life: |
|--|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300