## NSN 5945-01-210-9835

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-210-9835

Overall Length:
3.240 inches
Overall Diameter:
0.650 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately delicate
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Winding Dc Resistance Rating:
47.0 ohms all windings
Duty Type:
Intermittent
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
1 plug-in terminal single mounting facility
1 plug-in terminal single mounting facility  Storage Type:
1 plug-in terminal single mounting facility  Storage Type:  General purpose warehouse
1 plug-in terminal single mounting facility  Storage Type:  General purpose warehouse  Features Provided:
1 plug-in terminal single mounting facility  Storage Type:  General purpose warehouse  Features Provided:  Latching contacts
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary  Operating Voltage Rating And Type At Specificationified Temp:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius all windings
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius all windings  Main Contact Load Current Rating At Maximum Rated Voltage:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius all windings  Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius all windings  Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius all windings  Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts: 4000.0 ac and 4000.0 dc
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Features Provided: Latching contacts  Cubic Measure: 1.075 cubic inches  Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius all windings  Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts: 4000.0 ac and 4000.0 dc  Terminal Type And Quantity:

## NSN 5945-01-210-9835

Electromagnetic Relay - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A03300