NSN 5945-01-211-1524

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-211-1524		
Overall Length:		
1.718 inches		
Center To Center Distance Between Mounting Facilities Parallel To Length:		
0.625 inches single mounting facility		
Overall Height:		
1.320 inches		
Overall Width:		
1.035 inches		
Mounting Slot Width:		
0.150 inches single mounting facility		
Case Material:		
Metal		
Environmental Protection:		
Hermetic		
Fragility Factor:		
Moderately rugged		
Frequency In Hertz:		
400.0		
Winding Quantity:		
1		
Purpose For Which Designed:		
General		
Coil Quantity:		
1		
Duty Type:		
Continuous		
Arc Quenching Method:		
Air		
Mounting Facility Type And Quantity:		
3 slotted hole single mounting facility		
Storage Type:		
General purpose warehouse		
Features Provided:		

Polarized and coil voltage suppression

Cubic Measure:

2.347 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

40.0 milliamperes ac single winding

NSN 5945-01-211-1524

Electromagnetic Relay - Page 2 of 2



	Time	Del	lay:
--	------	-----	------

0.05 seconds fixed release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300