NSN 5945-01-211-2619

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-211-2619

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.734 inches
Overall Height:
2.281 inches
Overall Width:
1.531 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Winding Quantity:
1
1 Purpose For Which Designed:
•
Purpose For Which Designed:
Purpose For Which Designed: General
Purpose For Which Designed: General Coil Quantity:
Purpose For Which Designed: General Coil Quantity:
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating:
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 100.0 ohms single winding
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type:
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method:
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type:
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 100.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure: 6.055 cubic inches

Tillead Oize.

0.138 inches single mounting facility

NSN 5945-01-211-2619

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.028 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

30.0 amperes ac resistive load and 30.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Energizing Element Power Rating:

1.5 watts

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300