NSN 5945-01-211-4037

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-211-4037
Overall Length:
0.810 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.500 inches single mounting facility
Overall Height:
0.850 inches
Overall Width:
0.810 inches
Mounting Slot Width:
0.133 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
400.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized

Cubic Measure:

0.881 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

81.0 milliamperes dc single winding

NSN 5945-01-211-4037

Electromagnetic Relay - Page 2 of 2



Criticality Code Justification:
Feat
Time Delay:
0.006 seconds fixed operate and release time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.062 inches single mounting facility and 1.078 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
1.0 amperes ac lamp load and 1.0 amperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
200.0 ac and 28.0 dc
Special Features:
Failure rate level 0.5 percent
Test Data Document:
81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 wire hook all functions
Specification Data:
81349-mil-r-6106/28 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300