## NSN 5945-01-211-7748

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-211-7748

| Overall Length:   |  |  |  |
|---|--|--|--|
| 0.370 inches  |  |  |  |
| Overall Height:   |  |  |  |
| 0.375 inches  |  |  |  |
| Overall Width:  |  |  |  |
| 0.370 inches  |  |  |  |
| Case Material:  |  |  |  |
| Metal   |  |  |  |
| Environmental Protection:                                     |  |  |  |
| Hermetic  |  |  |  |
| Fragility Factor:   |  |  |  |
| Moderately rugged   |  |  |  |
| Winding Quantity:   |  |  |  |
| 1   |  |  |  |
| Purpose For Which Designed:                                   |  |  |  |
| General   |  |  |  |
| Coil Quantity:  |  |  |  |
| 1   |  |  |  |
| Winding Dc Resistance Rating:                                 |  |  |  |
| 800.0 ohms single winding                                     |  |  |  |
| Duty Type:  |  |  |  |
| Continuous  |  |  |  |
| Arc Quenching Method:   |  |  |  |
| Air   |  |  |  |
| Mounting Facility Type And Quantity:                          |  |  |  |
| 1 terminal single mounting facility                           |  |  |  |
| Storage Type:   |  |  |  |
| General purpose warehouse                                     |  |  |  |
| Cubic Measure:  |  |  |  |
| 0.051 cubic inches  |  |  |  |
| Nonpile-up Main Contact Arrangement:                          |  |  |  |
| 2 pole, double throw, one position momentary                  |  |  |  |
| Time Delay:   |  |  |  |
| 0.0075 seconds fixed release time                             |  |  |  |
| Operating Voltage Rating And Type At Specificationified Temp: |  |  |  |
| 12.0 volts dc 25 degrees celsius single winding               |  |  |  |
| Main Contact Load Current Rating At Maximum Rated Voltage:    |  |  |  |
| 100.0 milliamperes dc lamp load                               |  |  |  |
| Main Contact Maximum Voltage Rating In Volts:                 |  |  |  |
| 115.0 ac and 28.0 dc  |  |  |  |
| Precious Material And Location:                               |  |  |  |

Terminal surfaces gold

## NSN 5945-01-211-7748

Electromagnetic Relay - Page 2 of 2



| Precious |  | Material: |
|----------|--|-----------|
| _        |  |           |

Gold

**Terminal Type And Quantity:** 

8 wire lead all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300