# NSN 5945-01-212-0146

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-212-0146

## **Overall Length:**

2.750 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.647 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility

#### **Overall Height:**

2.234 inches

**Overall Width:** 

2.625 inches

**Case Material:** 

Plastic

**Environmental Protection:** 

Dustproof

**Unthreaded Mounting Hole Diameter:** 

0.144 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

# Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

# Winding Dc Resistance Rating:

49.1 ohms single winding

## Duty Type:

Continuous

# Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

# Pile-up Main Contact Form Arrangement:

12c

## Storage Type:

General purpose warehouse

#### **Features Provided:**

Polarized

## **Cubic Measure:**

16.127 cubic inches

#### Mounting Facility Pattern:

Rectangular single mounting facility

# NSN 5945-01-212-0146

Electromagnetic Relay - Page 2 of 2



**Operating Current Rating And Type:** 244.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load and 5.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Terminal Type And Quantity:** 38 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300