NSN 5945-01-212-7256

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-212-7256 **Thread Class:** 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 1.075 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.562 inches single mounting facility **Overall Height:** 1.510 inches **Overall Width:** 0.905 inches **Case Material:** Metal **Environmental Protection:** Hermetic Center To Center Distance Between Mounting Facilities Parallel To Height: 0.750 inches single mounting facility **Fragility Factor:** Moderately rugged Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 5.5 kilohms single winding **Duty Type:** Continuous **Arc Quenching Method: Mounting Facility Type And Quantity:** 2 threaded stud single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 1.469 cubic inches Thready Qty Per Inch (tpi):

Thread Size:

0.138 inches single mounting facility

32 single mounting facility

NSN 5945-01-212-7256

Electromagnetic Relay - Page 2 of 2



Mountir	ng	Fa	cility	Patter	n
			_		_

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.0085 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Deminitarizat

No **Fiig:**

A03300