# NSN 5945-01-213-1817

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-213-1817

## **Overall Length:**

6.000 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility

## **Overall Height:**

3.250 inches

## **Overall Width:**

4.500 inches

#### **Case Material:**

Metal

#### **Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:** 

0.201 inches single mounting facility

#### **Fragility Factor:**

## Moderately rugged

Frequency In Hertz:

60.0

## Winding Quantity:

1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

## Duty Type:

Continuous

Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

87.750 cubic inches

#### **Mounting Facility Pattern:**

Triangle single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally closed, double break, momentary action and 2 pole, single throw, normally open, double make, momentary action

#### Time Delay:

0.20 seconds fixed operate and release time

#### Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.120 inches single mounting facility

## NSN 5945-01-213-1817

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300