# NSN 5945-01-213-6130

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-213-6130

## Thread Class:

2a single mounting facility

## **Thread Direction:**

Right-hand single mounting facility

## **Overall Length:**

2.270 inches

## **Overall Height:**

1.687 inches

## **Overall Width:**

1.468 inches

**Case Material:** 

Plastic

## **Environmental Protection:**

Dustproof

## Fragility Factor:

Moderately rugged

#### **Contact Material:**

Silver

## Winding Quantity:

1

## **Purpose For Which Designed:**

General

## **Coil Quantity:**

1

# Winding Dc Resistance Rating:

472.0 ohms single winding

# Duty Type:

Continuous

# Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

# Storage Type:

General purpose warehouse

# Cubic Measure:

5.622 cubic inches

# Thready Qty Per Inch (tpi):

32 single mounting facility

# Thread Size:

0.138 inches single mounting facility

# Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

# NSN 5945-01-213-6130

Electromagnetic Relay - Page 2 of 2



**Operating Current Rating And Type:** 51.0 milliamperes dc single winding **Time Delay:** 0.015 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 240.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 4 quick disconnect, male all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig:

A03300