

View Online at <https://aerobasegroup.com/nsn/5945-01-213-8358>

**Overall Length:**

6.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility

**Overall Height:**

4.750 inches

**Overall Width:**

2.875 inches

**Case Material:**

Metal

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.219 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**End Application:**

For lubepack assembly

**Frequency In Hertz:**

60.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

83.644 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

110.0 ac and 440.0 ac

**Operating Voltage Rating And Type At Specificationified Temp:**

110.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

45.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

440.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

15.0 probe ac inductive load and 6.0 probe ac inductive load

**Special Features:**

Number of interlocks 2 normally open and 2 normally closed

**Terminal Type And Quantity:**

10 screw all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300