NSN 5945-01-213-8358

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-213-8358

Overall Length:
6.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.750 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches single mounting facility
Overall Height:
4.750 inches
Overall Width:
2.875 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.219 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
For lubepack assembly
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
83.644 cubic inches

Rectangular single mounting facility

Mounting Facility Pattern:

Nonpile-up Main Contact Arrangement:

4 pole, single throw, normally open, momentary action

NSN 5945-01-213-8358

Electromagnetic Relay - Page 2 of 2



Auxiliary Contact Maximum Voltage Rating In Volts:

110.0 ac and 440.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

45.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

15.0 probe ac inductive load and 6.0 probe ac inductive load

Special Features:

Number of interlocks 2 normally open and 2 normally closed

Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300