

View Online at <https://aerobasegroup.com/nsn/5945-01-214-0382>

**Overall Length:**

1.320 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.062 inches single mounting facility and 1.078 inches single mounting facility

**Overall Height:**

0.600 inches

**Overall Width:**

0.410 inches

**Mounting Slot Width:**

0.120 inches single mounting facility

**Environmental Protection:**

Hermetic and shock resistant and vibration resistant

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

700.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 slotted hole single mounting facility

**Features Provided:**

Coil voltage suppression

**Mounting Facility Pattern:**

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Criticality Code Justification:**

Feat

**Time Delay:**

0.005 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

160.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Special Features:**

Failure rate level 0.1 percent

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire hook all functions

**Specification Data:**

81349-mil-r-39016/22 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300