NSN 5945-01-214-0633



| Electromagnetic Relay - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5945-01-214-0633 |
| Thread Class: |
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.165 inches |
| Overall Height: |
| 1.397 inches |
| Overall Width: |
| 0.735 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 threaded stud single mounting facility |
| Storage Type: |
| |

General purpose warehouse

Cubic Measure:

1.196 cubic inches

Thready Qty Per Inch (tpi):

48 single mounting facility

Thread Size:

0.099 inches single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

NSN 5945-01-214-0633

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300