NSN 5945-01-214-2271



Electromagnetic Relay - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-01-214-2271 **Thread Class:** 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 1.531 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.187 inches single mounting facility **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.187 inches single mounting facility **Overall Height:** 2.320 inches **Overall Width:** 1.531 inches **Case Material:** Metal **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged **End Application:** Bow thruster Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity: Duty Type:** Continuous **Arc Quenching Method: Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility **Storage Type:** General purpose warehouse **Features Provided:** Latching contacts **Cubic Measure:**

Thready Qty Per Inch (tpi): 32 single mounting facility

5.438 cubic inches

NSN 5945-01-214-2271

Electromagnetic Relay - Page 2 of 2



Th	reac	l Si	76.

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.30 seconds adjustable operate time and 3.00 seconds adjustable operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

16 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300