NSN 5945-01-215-3148

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-215-3148 **Overall Length:** 0.810 inches **Overall Height:** 0.600 inches **Overall Width:** 0.410 inches **Case Material:** Metal **Environmental Protection:** Dustproof **Fragility Factor:** Moderately rugged Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 310.0 ohms single winding **Duty Type:** Continuous **Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 1 terminal single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 0.199 cubic inches **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Criticality Code Justification:** Feat Time Delay: 0.006 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

NSN 5945-01-215-3148

Electromagnetic Relay - Page 2 of 2



_			_			
v.	nac	ıaı	Fea	+11	ľΩ	۰.
u	ner	ıaı	ı ca	LU		Э.

Failure rate level 1.0 percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-39016/44 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300