# NSN 5945-01-215-3148

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-215-3148 **Overall Length:** 0.810 inches **Overall Height:** 0.600 inches **Overall Width:** 0.410 inches **Case Material:** Metal **Environmental Protection:** Dustproof **Fragility Factor:** Moderately rugged Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 310.0 ohms single winding **Duty Type:** Continuous **Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 1 terminal single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 0.199 cubic inches **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Criticality Code Justification:** Feat Time Delay: 0.006 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# NSN 5945-01-215-3148

Electromagnetic Relay - Page 2 of 2



_			_			
v.	nac	ıaı	Fea	+11	ľΩ	۰.
u	ner	ıaı	ı ca	LU		Э.

Failure rate level 1.0 percent

#### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

8 wire hook all functions

## **Specification Data:**

81349-mil-r-39016/44 professional/industrial association specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300