NSN 5945-01-216-0877

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-216-0877

Overall Length:
0.770 inches
Overall Height:
0.290 inches
Overall Width:
0.300 inches
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
450.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 printed circuit terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized and electrostatic shield and coil voltage suppression
Cubic Measure:
0.101 cubic inches
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
5.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
500.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
100.0 dc
Test Data Document:
81349-mil-r-83516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 pin energizing element and contacts

81349-mil-r-83516/4 government specification

Specification Data:

NSN 5945-01-216-0877

Reed Relay - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300