NSN 5945-01-216-0877

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-216-0877

Overall Length:

0.770 inches

Overall Height:

0.290 inches

Overall Width:

0.300 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

450.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized and electrostatic shield and coil voltage suppression

Cubic Measure:

0.101 cubic inches

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

5.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

100.0 dc

Test Data Document:

81349-mil-r-83516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 pin energizing element and contacts

Specification Data:

81349-mil-r-83516/4 government specification

NSN 5945-01-216-0877

Reed Relay - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

