NSN 5945-01-216-6145

Electromagnetic Relay - Page 1 of 2

2.100 inches single mounting facility

Overall Length: 2.431 inches

Overall Height: 2.010 inches



View Online at https://aerobasegroup.com/nsn/5945-01-216-6145

Center To Center Distance Between Mounting Facilities Parallel To Length:

| Overall Width: |
|---|
| 2.156 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Dustproof |
| Unthreaded Mounting Hole Diameter: |
| 0.099 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Frequency In Hertz: |
| 400.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 10.534 cubic inches |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Time Delay: |
| 0.015 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| |

NSN 5945-01-216-6145

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

200.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 32.0 dc

Terminal Type And Quantity:

5 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300