## NSN 5945-01-216-6171

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-216-6171

view Online at https://aerobasegroup.com/nsn/5945-01-216-6171
Overall Length:
6.060 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.500 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.500 inches single mounting facility
Overall Height:
4.120 inches
Overall Width:
4.060 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.196 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Power panel
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
101.366 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility

**Nonpile-up Auxiliary Contact Arrangement:** 

**Nonpile-up Main Contact Arrangement:** 

1 pole, double throw, one position momentary

3 pole, single throw, normally open, momentary action

## NSN 5945-01-216-6171

Electromagnetic Relay - Page 2 of 2



Auxiliary Contact Maximum Voltage Rating In Volts:
28.0 dc
Operating Voltage Pating And Type At Specification

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

28.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:** 

5.0 probe dc resistive load

**Terminal Type And Quantity:** 

11 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300