NSN 5945-01-216-6174

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-216-6174

| Overall Length: |
|---|
| 5.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.000 inches single mounting facility |
| Overall Height: |
| 5.138 inches |
| Overall Width: |
| 5.250 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.219 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| An/spn-35a lh |
| Frequency In Hertz: |
| 400.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 144.987 cubic inches |

Mounting Facility Pattern:
Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

NSN 5945-01-216-6174

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

47.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Terminal Type And Quantity:

6 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300