# NSN 5945-01-217-3387

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-217-3387

## **Overall Length:**

7.500 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

6.625 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility

### **Overall Height:**

5.156 inches

**Overall Width:** 

4.250 inches

Case Material:

Metal

**Environmental Protection:** 

Dustproof

**Unthreaded Mounting Hole Diameter:** 

0.250 inches single mounting facility

#### Fragility Factor:

Moderately rugged

### End Application:

Starter motor

#### Frequency In Hertz:

60.0

#### Winding Quantity:

1

#### Purpose For Which Designed:

General

#### **Coil Quantity:**

1

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Cubic Measure:

164.347 cubic inches

## Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

# NSN 5945-01-217-3387

Electromagnetic Relay - Page 2 of 2



#### Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

90.0 amperes ac resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac

## Terminal Type And Quantity:

4 screw all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300