NSN 5945-01-217-8554

Electromagnetic Relay - Page 1 of 2

81349-mil-r-83725/7 government specification

Overall Length:



View Online at https://aerobasegroup.com/nsn/5945-01-217-8554

1.900 inches
Overall Diameter:
0.680 inches
Case Material:
Glass and plastic
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
290.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Storage Type:
General purpose warehouse
Cubic Measure:
0.690 cubic inches
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Time Delay:
0.01 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
12.0 amperes ac resistive load and 12.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
36000.0 ac and 36000.0 dc
Test Data Document:
81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 turret energizing element
Specification Data:

NSN 5945-01-217-8554

Electromagnetic Relay - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300