# NSN 5945-01-218-3810

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-218-3810

## **Overall Length:**

3.125 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

#### **Overall Height:**

2.844 inches

**Overall Width:** 

1.031 inches

#### **Case Material:**

Metal

**Environmental Protection:** 

Dustproof

#### **Unthreaded Mounting Hole Diameter:**

0.199 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## **Contact Material:**

Gold

## End Application:

Depotteststat

### Winding Quantity:

1

# Purpose For Which Designed:

General

## **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

# Storage Type:

General purpose warehouse

## Cubic Measure:

9.163 cubic inches

## Mounting Facility Pattern:

Rectangular single mounting facility

# Nonpile-up Main Contact Arrangement:

24 pole, double throw, one position momentary

# NSN 5945-01-218-3810

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.025 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

**Precious Material And Location:** 

Contacts gold

**Precious Material:** 

Gold

**Terminal Type And Quantity:** 

74 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300