NSN 5945-01-218-5427

Electromagnetic Relay - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5945-01-218-5427

| 1.280 inches |
|--------------------------------------------------------------------------|
| Center To Center Distance Between Mounting Facilities Parallel To Length |
| 1.078 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.405 inches single mounting facility |
| Overall Height: |
| 0.810 inches |
| Overall Width: |
| 0.640 inches |
| Mounting Slot Width: |
| 0.133 inches single mounting facility |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| Hoist rescue |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 400.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 slotted hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 0.663 cubic inches |
| Mounting Facility Pattern: |

Nonpile-up Main Contact Arrangement:
3 pole, double throw, one position momentary

Rectangular single mounting facility

NSN 5945-01-218-5427

Electromagnetic Relay - Page 2 of 2



| Criticality Code Justification: |
|---------------------------------------------------------------------------------------------------------------------------------------------|
| Feat |
| Time Delay: |
| 0.006 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes ac lamp load and 2.0 amperes dc lamp load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Special Features: |
| Failure rate level 0.5 percent |
| Test Data Document: |
| 81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 11 wire hook all functions |
| Specification Data: |
| 81349-mil-r-6106/29 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A03300 |
| |
| |
| |