NSN 5945-01-218-5436

Electromagnetic Relay - Page 1 of 2

Overall Length: 6.375 inches



View Online at https://aerobasegroup.com/nsn/5945-01-218-5436

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 4.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.000 inches single mounting facility |
| Overall Height: |
| 5.000 inches |
| Overall Width: |
| 4.500 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Dustproof |
| Unthreaded Mounting Hole Diameter: |
| 0.219 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 143.437 cubic inches |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, single throw, normally open, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |

120.0 volts ac 25 degrees celsius single winding

NSN 5945-01-218-5436

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300