

View Online at <https://aerobasegroup.com/nsn/5945-01-218-7925>

**Overall Length:**

3.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.875 inches single mounting facility

**Overall Height:**

2.843 inches

**Overall Width:**

3.500 inches

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.218 inches single mounting facility

**Fragility Factor:**

Moderately delicate

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

44.5 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

36.071 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, double make, momentary action

**Time Delay:**

0.03 seconds fixed operate and release time

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 amperes ac resistive load and 100.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

25.0 amperes ac resistive load and 25.0 amperes dc resistive load

**Terminal Type And Quantity:**

2 screw energizing element

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300