## NSN 5945-01-218-7928

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-218-7928

| Overall Length:   |  |  |  |  |  |
|---|--|--|--|--|--|
| 4.800 inches  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |  |  |  |  |  |
| 3.600 inches single mounting facility                                     |  |  |  |  |  |
| Overall Height:   |  |  |  |  |  |
| 6.110 inches  |  |  |  |  |  |
| Overall Width:  |  |  |  |  |  |
| 3.212 inches  |  |  |  |  |  |
| Case Material:  |  |  |  |  |  |
| Metal   |  |  |  |  |  |
| Environmental Protection:   |  |  |  |  |  |
| Dustproof   |  |  |  |  |  |
| Unthreaded Mounting Hole Diameter:  |  |  |  |  |  |
| 0.388 inches single mounting facility                                     |  |  |  |  |  |
| Fragility Factor:   |  |  |  |  |  |
| Moderately rugged   |  |  |  |  |  |
| End Application:  |  |  |  |  |  |
| Starter motor   |  |  |  |  |  |
| Frequency In Hertz:   |  |  |  |  |  |
| 60.0  |  |  |  |  |  |
| Winding Quantity:   |  |  |  |  |  |
| 1   |  |  |  |  |  |
| Purpose For Which Designed:   |  |  |  |  |  |
| General   |  |  |  |  |  |
| Coil Quantity:  |  |  |  |  |  |
| 1   |  |  |  |  |  |
| Duty Type:  |  |  |  |  |  |
| Continuous  |  |  |  |  |  |
| Arc Quenching Method:   |  |  |  |  |  |
| Air   |  |  |  |  |  |
| Mounting Facility Type And Quantity:                                      |  |  |  |  |  |
| 2 unthreaded hole single mounting facility                                |  |  |  |  |  |
| Storage Type:   |  |  |  |  |  |
| General purpose warehouse   |  |  |  |  |  |
| Cubic Measure:  |  |  |  |  |  |
| 94.901 cubic inches   |  |  |  |  |  |
| Mounting Facility Pattern:  |  |  |  |  |  |
| In-line single mounting facility  |  |  |  |  |  |
| Nonpile-up Main Contact Arrangement:                                      |  |  |  |  |  |
| 2 pole, single throw, normally closed, momentary action                   |  |  |  |  |  |
| Operating Voltage Rating And Type At Specificationified Temp:             |  |  |  |  |  |

120.0 volts ac 25 degrees celsius single winding

## NSN 5945-01-218-7928

Electromagnetic Relay - Page 2 of 2



|  | Main | Contact | <b>Load Curi</b> | rent Rating | At Ma | ximum | Rated ' | Voltage: |
|--|------|---------|------------------|-------------|-------|-------|---------|----------|
|--|------|---------|------------------|-------------|-------|-------|---------|----------|

25.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

430.0 ac

**Terminal Type And Quantity:** 

6 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A03300