

View Online at <https://aerobasegroup.com/nsn/5945-01-218-8313>

Overall Length:

3.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility

Overall Height:

2.875 inches

Overall Width:

3.280 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Coil voltage suppression

Cubic Measure:

34.184 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

Operating Current Rating And Type:

200.0 milliamperes ac single winding

Time Delay:

0.03 seconds fixed operate and release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes ac resistive load and 100.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load and 25.0 amperes dc resistive load

Terminal Type And Quantity:

2 screw energizing element

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300