## NSN 5945-01-218-8314

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-218-8314

| Overall Length:   |  |  |  |
|---|--|--|--|
| 3.625 inches  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |  |  |  |
| 2.750 inches single mounting facility                                     |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |  |  |  |
| 1.875 inches single mounting facility                                     |  |  |  |
| Overall Height:   |  |  |  |
| 2.843 inches  |  |  |  |
| Overall Width:  |  |  |  |
| 3.300 inches  |  |  |  |
| Case Material:  |  |  |  |
| Metal   |  |  |  |
| Environmental Protection:   |  |  |  |
| Hermetic  |  |  |  |
| Unthreaded Mounting Hole Diameter:  |  |  |  |
| 0.218 inches single mounting facility                                     |  |  |  |
| Fragility Factor:   |  |  |  |
| Moderately rugged   |  |  |  |
| Winding Quantity:   |  |  |  |
| 1   |  |  |  |
| Purpose For Which Designed:   |  |  |  |
| General   |  |  |  |
| Coil Quantity:  |  |  |  |
| 1   |  |  |  |
| Duty Type:  |  |  |  |
| Continuous  |  |  |  |
| Arc Quenching Method:   |  |  |  |
| Air   |  |  |  |
| Mounting Facility Type And Quantity:                                      |  |  |  |
| 4 unthreaded hole single mounting facility                                |  |  |  |
| Storage Type:   |  |  |  |
| General purpose warehouse   |  |  |  |
| Features Provided:  |  |  |  |
| Coil voltage suppression  |  |  |  |
| Cubic Measure:  |  |  |  |
| 34.009 cubic inches   |  |  |  |
| Mounting Facility Pattern:  |  |  |  |
| Rectangular single mounting facility                                      |  |  |  |
| Nonpile-up Main Contact Arrangement:                                      |  |  |  |
| 3 pole, single throw, normally open, double make, momentary action        |  |  |  |
| Operating Current Rating And Type:  |  |  |  |
| 200 0 milliamperes ac single winding                                      |  |  |  |

## NSN 5945-01-218-8314

Electromagnetic Relay - Page 2 of 2



|  | Time | e De | elay: |
|--|------|------|-------|
|--|------|------|-------|

0.03 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes ac resistive load and 100.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

2 screw energizing element

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300