## NSN 5945-01-220-8460

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-220-8460
Overall Length:
1.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.437 inches single mounting facility
Overall Height:
1.612 inches
Overall Width:
0.525 inches
Mounting Slot Width:
0.150 inches single mounting facility
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
6.84 kilohms single winding and 8.36 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
1.5 amperes ac motor load and 3.0 amperes dc motor load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Test Data Document:
81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 tab, solder lug all functions
Specification Data:
81349-mil-r-5757/23 government specification
Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5945-01-220-8460

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300