NSN 5945-01-221-2325

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-221-2325

Overall Length:
2.780 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility
Overall Height:
5.700 inches
Overall Width:
2.780 inches
Environmental Protection:
Fungus resistant and water resistant and salt spray resistant
Unthreaded Mounting Hole Diameter:
0.120 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Mc-1a motor g
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
44.052 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
7 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

NSN 5945-01-221-2325

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts	Main	Contact	Maximum	Voltage	Rating	In	Volts:
--	------	---------	---------	---------	--------	----	--------

600.0 ac and 230.0 dc

Terminal Type And Quantity:

18 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300