## NSN 5945-01-221-3960

Electromagnetic Relay - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5945-01-221-5960
Overall Length:
0.810 inches
Overall Height:
0.617 inches
Overall Width:
0.410 inches
Environmental Protection:
Hermetic
Winding Quantity:
2
Coil Quantity:
2
Winding Dc Resistance Rating:
1.0 kilohms all windings
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Features Provided:
Latching contacts and polarized
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.005 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius all windings
Main Contact Load Current Rating At Maximum Rated Voltage:
150.0 milliamperes ac resistive load and 2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Failure rate level 3.0 percent
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
10 pin all functions
Specification Data:
81349-mil-r-39016/45 government specification

N/a

Shelf Life:

## NSN 5945-01-221-3960

Electromagnetic Relay - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A03300