

View Online at <https://aerobasegroup.com/nsn/5945-01-221-5403>

**Overall Length:**

3.620 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.640 inches first mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.640 inches first mounting facility

**Overall Width:**

2.430 inches

**Overall Diameter:**

2.810 inches

**Unthreaded Mounting Hole Diameter:**

0.196 inches second mounting facility

**Contact Material:**

Silver

**End Application:**

6525-01-159-3009, field radiographic/fluoroscopic x-ray system; model 350 ii

**Frequency In Hertz:**

Between 50.0 and 60.0

**Purpose For Which Designed:**

Specific

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 unthreaded hole first mounting facility

**Mounting Facility Pattern:**

In-line first mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, double make, momentary action

**Operating Voltage Rating And Type At Specificationified Temp:**

230.0 volts ac nonstandard temp all windings

**Main Contact Load Current Rating At Maximum Rated Voltage:**

25.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

230.0 ac

**Special Features:**

Relay has (12) auxiliary quick-connect terminals

**Precious Material And Weight:**

0.020 silver ounces, troy

**Precious Material:**

Silver

**Terminal Type And Quantity:**

4 tab w/screw energizing element

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300