

View Online at <https://aerobasegroup.com/nsn/5945-01-221-5403>

Overall Length:

3.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.640 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.640 inches first mounting facility

Overall Width:

2.430 inches

Overall Diameter:

2.810 inches

Unthreaded Mounting Hole Diameter:

0.196 inches second mounting facility

Contact Material:

Silver

End Application:

6525-01-159-3009, field radiographic/fluoroscopic x-ray system; model 350 ii

Frequency In Hertz:

Between 50.0 and 60.0

Purpose For Which Designed:

Specific

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole first mounting facility

Mounting Facility Pattern:

In-line first mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

230.0 volts ac nonstandard temp all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

230.0 ac

Special Features:

Relay has (12) auxiliary quick-connect terminals

Precious Material And Weight:

0.020 silver ounces, troy

Precious Material:

Silver

Terminal Type And Quantity:

4 tab w/screw energizing element

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300