NSN 5945-01-221-8975

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-221-8975

Overall Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches single mounting facility

Overall Height:

2.500 inches

Overall Width:

2.500 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.187 inches single mounting facility

Contact Material:

Silver

Contact Surface Treatment:

Cadmium plated

End Application:

6525-01-159-3009; end item name: field radiographic x-ray system, model dxd 350 ii

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

4410

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Intermittent

Arc Quenching Method:

Magnetic

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

2c

Cubic Measure:

56.025 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Operating Current Rating And Type:

25.0 amperes ac all windings

NSN 5945-01-221-8975

Electromagnetic Relay - Page 2 of 2



Auxiliary Contact Maximum Voltage Rating In Volts:
120.0 ac
Main Contact Load Current Rating At Maximum Rated Voltage:
25.0 amperes ac inductive load
Main Contact Maximum Voltage Rating In Volts:
277.0 ac
Auxiliary Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes ac resistive load
Special Features:
Assembled with auxiliary contact
Precious Material And Location:
Contacts silver
Precious Material And Weight:
0.042 silver ounces, troy
Precious Material:
Silver
Terminal Type And Quantity:
8 screw all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300